

PATHFINDER EMERGENCY LIGHT GEN2

PRODUCT DETAILS



Rated life: L70 B50 50000hrs
 Driver: Remote, Non-Dim
 Rating: IP20, Class II
 Operating temperature: 0°C to +40°C
 Housing: Polycarbonate (PC)
 Finishing: White/Black
 Accessory (order separately): Surface mount kit, Vandal-proof kit
 Emergency: Non-Maintained, Manual test, Replaceable lithium iron phosphate (LiFePO4) battery, 18 months shelf life
 Compliant: AS/NZS 2293, D80 emergency classification
 Warranty: 5 years on fixture and lamp, 4 years on battery

MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

DALI emergency (self-test if not connected to DALI)

APPLICATIONS

Recessed (ceiling), Internal
 Office spaces, Fire passages, Retail centres, Aged care, Hospitality, Correctional facilities



CODE	DESCRIPTION	POWER~	LUMENS*	EFFICACY	WEIGHT
PFLED-RL2	PATHFINDER GEN2 RECESSED D80 5W NON-MAINTAINED EMERGENCY WHITE	5W	436LM	87LM/W	0.3KG
PFLED-RLBK2	PATHFINDER GEN2 RECESSED D80 5W NON-MAINTAINED EMERGENCY BLACK	5W	436LM	87LM/W	0.3KG
PFDLED-RL2	PATHFINDER GEN2 RECESSED D80 5W NON-MAINTAINED DALI EMERGENCY WHITE	5W	452LM	87LM/W	0.3KG
PFDLED-RLBK2	PATHFINDER GEN2 RECESSED D80 5W NON-MAINTAINED DALI EMERGENCY BLACK	5W	452LM	87LM/W	0.3KG
PFSKIT-L2	PATHFINDER GEN2 SURFACE MOUNT KIT WHITE				
PFSKIT-LBK2	PATHFINDER GEN2 SURFACE MOUNT KIT BLACK				
FFLEDVK	PATHFINDER GEN2 VANDAL-PROOF KIT				

~ Tested system powers from luminaire. *Delivered lumens from luminaire, including thermal, electrical and optic losses. ^Figures are interpolated / extrapolated from data at other versions.